

Item	Qty	Description
------	-----	-------------

EQUIPMENT AS PER GS CATERING DRAWING NO: 6129 - 01

1		ITEM OMITTED
2		ITEM OMITTED
3		ITEM BY OTHERS EPOS System
4	1 ea	BACK BAR CABINET, REFRIGERATED  Other GL001 Polar Back Bar Cooler, one-section, 600mm, 138 litre capacity, (1) hinged double glazed glass door with lock & auto-close, (2) adjustable shelves, integral temperature controller, 2°C to 8°C temperature range, forced air cooling, automatic defrost, R600a, adjustable feet, aluminium interior, black painted steel exterior, 230v/50, 1.3 amps, 180 watts
5		ITEM OMITTED
6		ITEM OMITTED
7		ITEM OMITTED
8	1 ea	REFRIGERATOR, UNDERCOUNTER Other CD080 St/st undercounter refridgerator, 150 ltr, LED digital temperature display, lockable.
9		ITEM OMITTED
10	1 ea	L-SHAPED SERVERY Bespoke Fabrication FABRICATION "L" shaped St/Steel topped counter measuring approx 2000/2800 x 800 x 900 mm high, comprising of the following sections reading left to right from the operators side: 3m LAM The counter is finished in a single colour laminate to exposed front and end , priced with a choice from Polyrey Classique range, or Merinolam plain colours, patterns & woods. 5m K/T St/steel kick strip to all exposed sides, price per metre Section A UM ambient plain top section, open under with base and mid shelves where possible Part void to L/H/E PORT Inset cable port hole to above section.

SINGLE Switched RCD socket outlet - single [wired]

TWIN Switched RCD socket outlet - Twin [wired]

Galvanised data back box [un-wired]

Section B

UMHD Approx 900mm Long Serving Counter, plain top, enclosed ambient base, (2) hinged rear doors, (1) stainless steel midshelf, stainless steel construction

Section C

Appox. 1000 mm long wall bench

Scrap hole in front of WHB over bin

Welded up with full void under for fridge and bin.

Weld in wash hand basin positioned to rear of bench

st/st Single Skin End Panel to R/H/E

1 ea Installation

11 1 ea **L-SHAPED SERVERY**

Bespoke Fabrication FABRICATION

St/Steel topped counter measuring x x mm high, comprising of the following sections reading left to right from the operators side:

Finished with st/st panels

4m K/T St/steel kick strip to all exposed sides, price per metre

Section A

Hot Cupboard, electric, 947mm W x 700mm D x 900mm H, flat insulated reinforced top, thermostatic controls, doors on one side, bright polished interior with (2) heavy duty shelves, removeable control panel and removeable fan assisted heating units, 5" castors, 0.9 kW, 13amp plug with a 2 mtr cable

Corner mitre, chamfer

Heated Overshelf, three tier, 876 x 311 x 942mm, independent dimmer control area on right, (6) 220 watts quartz lamps, stainless steel, 1.32 kW, cord & 13 amp plug

Section B

UM ambient plain top section

Part void

1 ea Installation

12 **ITEM OMITTED**

13 **ITEM OMITTED**

14 1 ea **MICROWAVE OVEN**



Regale Microwave Ovens R21AT

Sharp R-21AT Microwave Oven, 1000 watts (IEC 60705) microwave output power, 28 litre (1.0 cu. ft.) oven capacity, (20) memory settings, easy grip handle, double quantity facility, express defrost facility, solid stainless steel cavity/cabinet, 240v/50/1-ph, 1 year manufacturer's on-site warranty (NET)

1 ea Bespoke Fab FABRICATION Microwave Shelf, wall mounted, 500 x

15	1 ea	WALL STYLE VENTILATION CANOPY Other S1 Wall style extraction canopy measuring 2850 x 1450 x 500 mm featuring: • Made from dull buff stainless steel sheet with protective plastic coating, • 50 x 25 mm grease channel with fully-welded corners and easy-clean grease collection cups • Full-length, liquid-tight triangulated extraction plenum containing • 4 no. removable, polished stainless steel baffle filters suitable for cleaning in a commercial dishwasher, • Canopy supplied complete with galvanised spigots for connection to ductwork • Design duty extract TBA m3/s @ 140 Pa
	1 ea	REPLACEMENT AIR Replacement air system for the above canopy to deliver 75% to 85% of the extracted air volume, featuring: • Full-length insulated stainless steel plenum fitted to the front of the canopy incorporating • 2 no. perforated 'whisper-mesh' diffusers. • Supplied complete with galvanised spigots for connection to ductwork, • Design duty supply TBA m3/s @ 40 Pa
	1 ea	LIGHTING Lighting for the above canopy featuring: • 4 No. IP65 rated, 8.5W LED downlights to generate approximately 500 lux at the work surface • Pre-wired with heat resistant cable for connection to the local lighting circuit
	1 ea	CLADDING Stainless steel wall cladding for the above canopy featuring: • Dull buff stainless steel sheets, with polished jointing strips. • Cladding behind cooking equipment along full length of canopy and to one/both end(s) measuring 2850 x 2000mm • Coving section at floor/wall junction for easy cleaning.
	1 ea	EXTRACT FAN AND DUCTWORK Budget price based on approximately 10 metres of duct complete with bends to be confirmed on site survey and detailed design. Axial fan with appropriate speed controller. Design duty TBA m3/s @ 140 Pa
	1 ea	REPLACEMENT AIR FAN AND DUCTWORK Budget price based on approximately 10 metres of duct complete with bends to be confirmed on site survey and detailed design. Axial fan with appropriate speed controller. Design duty TBA m3/s @ 40 Pa. EU4 panel / bag dust filter to ensure that only clean air enters the kitchen,

NB: incoming air from this system is un-tempered unless a cost option for tempered air is selected. In the interests of staff comfort, we recommend that tempered air is actively considered.

1 ea Installation Included

15A 1 ea **FIRE SUPPRESSION SYSTEM**

Other ANSUL R102

The system shall be an Ansul R102 single tank fire suppression system which is mechanically operated, utilising automatic fusible link detectors, positioned within the cooker hood, plenum area. A manual release point shall also be provided adjacent to the kitchen exit.

Specification

The Ansul R102 Restaurant Fire Suppression System is designed to provide fire protection for restaurant cooking appliances, hoods and ducts. It is a pre-engineered group of mechanical and electrical components for installation by an authorised Ansul Distributor.

System Description

The basic system consists of an Ansul automan regulator which includes a regulator release mechanism and a liquid agent storage tank housed within a single enclosure. Nozzles, detectors, cartridges, liquid agent, fusible links, pulley tees and elbows are supplied in separate packages in the quantities needed for each of the fire suppression system arrangements.

Extinguishing Agent

The R102 system suppresses fire by spraying at the plenum area and filters, cooking surfaces and the exhaust duct system with a predetermined flow rate of Ansulex liquid. When the liquid agent is discharged onto a cooking appliance fire, it cools the grease surface and reacts with the grease (saponification) forming a soap like foam on the surface of the fat. This layer acts as insulation between the hot grease and the atmosphere, thus helping to prevent the escape of combustible vapour.

System Engineering

The Ansulex is stored in a 3 gallon agent storage tank. The tank is manufactured from stainless steel and is pressurised only when the system is actuated. Pressurisation of the tank is provided by a nitrogen cartridge which will vary in size according to the number of main agent tanks on the system.

The nitrogen is regulated down to 100 psi before it passes into the Ansulex tank, as the tank is pressured the Ansulex liquid is driven from the tank through the distribution pipework to the discharge nozzles so that it is applied directly onto the fire.

16 1 ea **WALL BENCH**

Bespoke Fabrication FABRICATION
 Wall Bench, 800 x 800 x 600 mm, 1.2mm thick 304 grade stainless steel top with 50 mm H backsplash, stainless steel undershelf, welded corners, stainless steel legs with adjustable feet 600 mm high upstand to rear and R/H/E blank rear of R/H upstand

17 1 ea **GRIDDLE, COUNTER UNIT, ELECTRIC**



Lincat GS4
 Silverlink 600 Griddle, electric, countertop, 450 mm, 12 mm thick machined steel plate, thermostatic control, single heat zone, splashguard, stainless steel construction, CE

18 1 ea **FRYER, COUNTER UNIT, ELECTRIC, SINGLE WELL**



Lincat DF39
 Silverlink 600 Fryer, electric, countertop, 300 mm, 9 litre capacity tank, thermostat control, (1) nickel plated wire basket, batter plates, stainless steel lid & construction, CE

19 1 ea **INDUCTION RANGE, FLOOR MODEL**



Lincat PHER02
 Phoenix Induction Range, electric, 600 mm, (4) 1.85 kW cooking zones with 3.0 kW boost in 2 zones, 6mm thick glass ceramic surface, automatic pan detection, fan assisted oven with thermostatic control, solid side hinged door, (3) 1/1 GN capacity, stainless steel construction, castors, 11.4 kW, IPX4, CE

1 ea Castors, standard

20 1 ea **COMBI OVEN, ELECTRIC, 1/1 GN**



Falcon Foodservice COES101R
 Lainox Compact by Sapiens® Reloaded Combi Oven, electric, direct steam, (10) 1/1 GN capacity, manual controls with programmable memory, LCS automatic cleaning system supplied with (1) cleaning cartridge, multipoint core probe, built-in hand shower, stainless steel construction, 15.5 kW, IPX5, CE

1 ea NPSB Right Hinged Door

1 ea CSR101 Floor Stand, stainless steel for COEN101/COES101

1 ea European WaterCare VAPOUR-3P-18-PK CTU Water Care Package, with spray arm, 16 litre, 3-port (inlet, outlet, and quench), for 10 grid combi oven, includes (1) CTU (Calcium Treatment Unit), (1) 3-port head, (3) 1 metre stainless steel braided hoses (3/4" 90° x 3/4" straight), water meter with link hose and water care pack, 13,648 litre capacity based on water hardness of 12° Clarke, for Kuppersbusch, Electrolux, and Rational Ovens (NET)

21 1 ea **WALL BENCH**

Bespoke Fabrication FABRICATION

		Wall Bench, 2100 x 700 x 900 mm, 1.2mm thick 304 grade stainless steel top with reinforced underskin & 50 mm H backsplash with 50mm turndown to front and ends, stainless steel undershelf, stainless steel legs with adjustable feet Part void Weld in bowl, size 450x450x300mm, Anti-drip mould to bowl Corner mitre, chamfer
	1 ea	Mechline WR-500MD Pegler (Comap) Dome Head Mixer Tap, deck mount, twin water feed, two controls, 1/2", WRAS
22	2 ea	WALL SHELF Bespoke Fabrication FABRICATION Wall Shelf, 1400 x 300 mm, 25 mm up-turn on rear, stainless steel, includes: (2) brackets
23	1 ea	REFRIGERATOR, UNDERCOUNTER Other CD080 St/st undercounter refridgerator, 150 ltr, LED digital temperature display, lockable.
24	1 ea	SLIM BIN Other F603 Rubbermaid Slim Jim Container Capacity : 60Ltr Dimensions : 632(H)x 588(W)x 279(D)mm
	1 ea	F634 Dolly for Slim Jim
25	2 ea	HAND WASH BASIN Mechline Developments WS2-L BaSiX Hand Wash Station, 305mm x 270mm x 140mm H overall, 240mm dia. x 135mm deep bowl, (2) 3" lever taps, includes: basin, drain boss, 304 stainless steel, WRAS
		
26	2 ea	FLY KILLER / KILLING GRID Mechline Developments CZPEPAT20S CZP Energy Pro 20 Stainless Steel, electric grid, Flying Insect Killer, 288mm W x 105mm D x 256mm H, 40-60 sq. meter range of action, (1) energy saving UV lamp with shatter-proof safety sheath, three-way fixing-hanging, wall-mounted, or stand-alone, UK moulded 3-pin plug, 220-240v/50/1-ph, 16.0 watts, 3 amps, plug and cord, CE, conforming to EU standards
		
27	1 ea	L SHAPED WALL BENCH Bespoke Fabrication FABRICATION "L" shaped wall bench 1500/1100 x 600 x 900 mm high Part void (void size to be advised with or before order) 2no Higher Upstand, per 300mm at 300mm high to R/H/E

Blank off rear of high upstand
 Corner mitre, chamfer
 Drop section to top, to one end, specify left or right

28	2 ea	WALL SHELF Bespoke Fabrication FABRICATION Wall Shelf, 1200 x 300 mm, 25 mm up-turn on rear, stainless steel, includes: (2) brackets
29	1 ea	REFRIGERATOR, UNDERCOUNTER Other CD080 St/st undercounter reffridgerator, 150 ltr, LED digital temperature display, lockable.
30	2 ea	WALL SHELF Bespoke Fabrication FABRICATION Wall Shelf, 600 x 300 mm, 25 mm up-turn on rear, stainless steel, includes: (2) brackets
31	1 ea	PLANETARY MIXER Pentland Wholesale Ltd FMX20 Planetary Mixer, silver, 20L bowl capacity, 5.0kg max flour capacity, (3) speed settings, safety stop function, 304 stainless steel bowl, lever operated bowl lift, bowl guard, supplied with wire whisk, dough hook & beater, 13 amp, 1100W
32	1 ea	SHELVING UNIT, WIRE EAIS EZN-4-6X6 EZ Store + Wire Shelving System, 4-tier, 600mm W x 600mm D x 1800mm H, 300kg weight load capacity per shelf, grey nylon coated shelves & poles
	1 ea	EZN-6X6 EZ Store + Wire Shelf, 600mm W x 600mm D, 300kg weight load capacity, grey nylon coated finish
33	1 ea	MOBILE INGREDIENT BIN 65LTR WHITE Other W777 Product features Capacity 65Ltr Dimensions 597(H) x 356(W) x 673(D) mm Material Polycarbonate Lid, Polyethylene Weight 10kg Colour White Heavy duty polythene with clear shatterproof flip lid. 4 x 3" swivel castors. 23.5 x 14 x 26.5" Colour coded
34	1 ea	FREEZER, UPRIGHT (REACH-IN)



Other G593

Polar Single Door Freezer, 680mm, 600 litre capacity, (1) hinged solid door with lock, (3) adjustable shelves & floor protector shelf, accommodates (10) 2/1 GN pans, fully automatic controller with digital display, -20°C to -10°C temperature range, fan assisted cooling, R290, lockable castors, aluminium interior, stainless steel exterior, 230v/50, 600 watts, MEPS D

35 1 ea

REFRIGERATOR, UPRIGHT (REACH-IN)



Other G592

Polar Single Door Fridge, one-section, 680mm, 600 litre capacity, (1) hinged solid door with lock, (3) adjustable shelves & floor protector shelf, accommodates (10) 2/1 GN pans, fully automatic controller with digital display, -2°C to 8°C temperature range, fan assisted cooling, off-cycle defrost, R600a, lockable castors, aluminium interior, stainless steel exterior, 230v/50, 300 watts, MEPS C

36 1 ea

SHELVING UNIT, WIRE



EAIS EZN-4-6X6

EZ Store + Wire Shelving System, 4-tier, 600mm W x 600mm D x 1800mm H, 300kg weight load capacity per shelf, grey nylon coated shelves & poles

1 ea

EZN-6X6 EZ Store + Wire Shelf, 600mm W x 600mm D, 300kg weight load capacity, grey nylon coated finish

37 1 ea

DISHWASHER, UNDERCOUNTER



Maidaid-Halcyon C525 WSD-DW

C Range Dishwasher, under counter, soft touch controls, (3) cycles, cycle times between 70-240 secs, wash tank 60°C (adjustable), rinse boiler 82°C (adjustable), built-in rinse aid & detergent dispenser, drain pump, breaktank, internal automatic water softener, includes: (1) 500 x 500mm open basket rack & (1) 500 x 500mm plate basket rack, height excludes adjustable feet which will add 10-20mm

1 ea

240v/50/1-ph, 6.5kW, 30.0 amps, standard

1 ea

Q902100B Universal Stand, 520mm high, adjustable stand, black powder coated steel

38 **ITEM OMITTED**

39 1 ea

DISHWASH TABLE

Bespoke Fabrication FABRICATION

Dishwash Tabling, 1200 mm, 304 stainless steel top, shelf under, 30 mm square section stainless steel legs with adjustable feet.

No entry to dishwasher.

Sink bowl comes with splashback, bowl size: 450 x450x300mm deep

		Welded up with full void under Corner mitre/chamfer
	1 ea	Mechline TX-PR-30D-ST-BF2 AquaTechnix Pre-Rinse Spray, deck mount, standard height, 180mm centers, 1187mm H, 300mm bowl filler, dome head controls, twin water feed & twin pedestal, spray gun, PosiStop™, 1.5-5 bar, 1/2" NPT, chrome finish, includes: restraining device, water saving face plate, "Kiwa KUKreg4 1+" approved
40	1 ea	SLIM BIN Other F603 Rubbermaid Slim Jim Container Capacity : 60Ltr Dimensions : 632(H)x 588(W)x 279(D)mm
	1 ea	F634 Dolly for Slim Jim
41	1 ea	DRAIN DOSING SYSTEM Mechline Developments GP-DMI-STD-2 GreasePaK Drain Maintenance System, BATTERY operated compact dosing module, requires GP-MSGD5 Bio-Enzymatic Dosing Fluid, 'fluid empty' audible alarm, key-lockable, CE, BBA
	1 ea	GP-MSGD5 Bio-Enzymatic Fluid Master Box, BBA, for GreasePaK Drain Maintenance System (packed 3 x 5 L boxes per master box - approximately 3 months supply)
42		ITEM OMITTED
43		ITEM OMITTED
44	1 ea	REFRIGERATOR, UNDERCOUNTER Other CD080 St/st undercounter refridgerator, 150 ltr, LED digital temperature display, lockable.
45	1 ea	INFIL BENCH Bespoke Fabrication FABRICATION Infill bench , 200 x 750 x 900 mm, 1.2mm thick 304 grade stainless steel top with 50 mm H backsplash, stainless steel undershelf, stainless steel legs with adjustable feet